

SCARLINE

LUBRICANTS & GREASE EXPERTS

DIAMOND PRO 0W-30 C2/C3 LONGLIFE

SCARLINE DIAMOND PRO 0W-30 C2/C3 LONGLIFE is a premium, fully synthetic, mid-SAPS engine oil specially formulated for modern gasoline and light-duty diesel engines equipped with Diesel Particulate Filters (DPF), Gasoline Particulate Filters (GPF), and three-way catalysts (TWC). Its advanced formulation delivers outstanding wear protection, excellent cleanliness, superior low-temperature performance, and fuel economy benefits. Designed to meet the latest OEM requirements, it provides reliable all-season protection and supports extended drain intervals when approved by the vehicle manufacturer.

Features and Benefits

- Provide fuel economy and energy conserving in EURO VI, EURO V and EURO IV Standard engines with normal and extended oil change intervals.
- Excellent piston and turbocharger cleanliness to reduce sludge and deposit formation.
- Outstanding wear protection for longer engine life under severe operating conditions.
- Fuel efficiency improvement through optimized friction reduction
- Advanced LSPI protection for modern gasoline direct-injection engines.

Specifications

Meets and Exceeds:

ACEA C2/C3; API: SP; SN & SN PLUS; MB 229.31/229.51/229.52; BMW LL04; Dexos 2; Ford WSS-M2C950-A; Renault RN0700; Renault RN0710; Volkswagen VW 504.00/507.00; Porsche C30; PSA B71 2390-2014; PSA B71 2312-2017; Fiat 9.55535-DS1; Fiat 9.55535-GS1, FORD WSS-M2C950-A, JAGUAR LAND ROVER STJLR .03.5007.

Technical Specifications

Test	Metot	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	10,0 - 12,2
Density @ 15°C g/ml	ASTM D4052	0,840 - 0,865
Viscosity Index	ASTM D2270	Min. 150
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max. -38
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0

Health & Safety

Avoid prolonged or repeated contact with used oil. Wash skin thoroughly after handling. Refer to the product's Safety Data Sheet (SDS) for more details.