

SCARLINE

LUBRICANTS & GREASE EXPERTS

DIAMOND PRO 5W-30 C2/C3 LONGLIFE

SCARLINE DIAMOND PRO 5W-30 C2/C3 LONGLIFE is a high-quality, mid-SAPS, fully synthetic engine oil made for modern gasoline and light-duty diesel engines with DPF, GPF, or three-way catalysts. It is ideal for cars and SUVs that need SAE 5W-30 oil meeting ACEA C2/C3 or VW 504 00 / 507 00 standards, including turbocharged direct-injection gasoline engines, Euro 5/6 diesel engines with DPF, and gasoline engines with GPF/TWC. This oil is designed to perform reliably all year round, whether driving in the city, on highways, or in high temperatures.

Features and Benefits

- Its low viscosity and low friction properties provide savings of up to 2% in fuel economy.
- Reduces risk of pre-ignition in modern turbocharged engines.
- Have excellent shear stability ensuring the oil maintains its grade throughout use.
- Provides superior performance under extreme cold start up conditions.
- Reduced oil consumption due to high-quality base oils and optimized volatility

Specifications

Meets and Exceeds:

API SP/ SN/CF;SN PLUS; ACEA C2/C3; MB 229.31; MB 229.51; MB 226.52; VW 504 00/507 00; BMW LL04; Dexos 2; Renault RN0700; Renault RN0710; RN17 level; Porsche C30; Fiat 9.55535-S3; Ford WSS-M2C917-A; PSA B71 2290; PSA B71 2297.

Technical Specifications

Test	Metot	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	10,0 - 12,2
Density @ 15°C g/ml	ASTM D4052	0,8450 - 0,870
Viscosity Index	ASTM D2270	Min. 140
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max. -35
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0

Health & Safety

Avoid prolonged or repeated contact with used oil. Wash skin thoroughly after handling. Refer to the product's Safety Data Sheet (SDS) for more details.