

SCARLINE

LUBRICANTS & GREASE EXPERTS

GOLD 5W-30 C3

SCARLINE GOLD 5W-30 C3 is a premium full-synthetic multigrade engine oil designed for high-performance gasoline and light- duty diesel engines. Formulated with high-quality base oils and advanced additive technology, it meets API SP ;SN PLUS and ACEA C3 specifications, offering excellent protection against wear, deposits, and sludge. This oil ensures reliable performance under low temperatures, making it suitable for year-round use in modern passenger cars and light commercial vehicles.

Features and Benefits

- Excellent wear protection for extended engine life.
- Enhanced engine cleanliness to reduce sludge and deposit formation.
- Stable viscosity for consistent performance in all temperatures.
- Superior oxidation stability for extended drain intervals.
- Fast lubrication at cold start-up to minimize wear.
- Reduced oil consumption due to low volatility formulation.
- Compatible with turbochargers and catalytic converters.
- All-season performance for a wide range of operating conditions.

Specifications

Meets and Exceeds:

API: SP; SN PLUS; SN/CF-4; ACEA:C3; VOLKSWAGEN VW 502.00/505.00 01; BMW LL-04; GM Dexos1, GEN 3; MB 229.51; MB 229.52; MB 229.31; MB 226.5; RENAULT RN0700; RENAULT RN0710; GM Dexos2; BMW LL-04; OPEL OV0401547; PSA 2290; FIAT 9.55535-S3.

Technical Specifications

Test	Metot	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	9,8 – 12,3
Density @ 15°C g/ml	ASTM D4052	0,870 - 0,885
Viscosity Index	ASTM D2270	Min. 120
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max. -30
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0

Health & Safety

Avoid prolonged or repeated contact with used oil. Wash skin thoroughly after handling. Refer to the product's Safety Data Sheet (SDS) for more details.