

SCARLINE

LUBRICANTS & GREASE EXPERTS

ATF DEXRON III

SCARLINE ATF DEXRON III is a high-performance automatic transmission fluid formulated with premium base oils and advanced additives to meet the requirements of General Motors DEXRON III and Ford MERCON specifications. It provides excellent protection against wear, oxidation, and corrosion, ensuring smooth and consistent shifting under all operating conditions. Its superior friction stability maintains transmission performance over extended drain intervals, while excellent low-temperature properties guarantee quick circulation and protection during cold starts.

Features and Benefits

- Meets GM DEXRON III & Ford MERCON performance requirements.
- Smooth and consistent shifting in all temperatures.
- Enhanced oxidation stability for longer fluid life.
- Outstanding wear protection for extended transmission service life.
- Superior friction retention for consistent performance.
- Excellent low-temperature flow for fast lubrication on cold starts.
- Protects against rust and corrosion in transmission components.
- Resists foaming for stable operation under high-speed conditions.
- Multipurpose use in transmissions, power steering, and certain hydraulic systems.

Specifications

Meets and Exceeds:

GM DEXRON IIIH; GM DEXRON IIIG; GM DEXRON IID; DTFR 13C170 (MB-Approval 236.9); DTFR 13C100 (MB 236.1); MAN 339 Type Z1/V1/L1; Ford Mercon; ALLISON C-4; CAT TO-2; ZF TE-ML-03D/04D/09/11A/14A/17C; VOLVO 97340/97341; Voith 55.6335.XX

Technical Specifications

Test	Methot	Typical Properties
Color	Visual	Red
Kinematic Viscosity (100°C), [cSt]	ASTM D445	7,2 - 8,2
Density @ 15°C g/ml	ASTM D4052	0,860 - 0,880
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max. -30

Health & Safety

Avoid prolonged or repeated contact with used oil. Wash skin thoroughly after handling. Refer to the product's Safety Data Sheet (SDS) for more details.